



## Ring Type Gasket Dimensions as per BS 10

Table A, D, E, F, H, J, K

NPS	d1	d2						
		Table	Table	Table	Table	Table	Table	Table
		A	D	E	F	H	J	K
1/2	21	52	52	52	52	65	65	65
3/4	27	59	59	59	59	65	65	65
1	34	68	68	68	70	70	70	78
1¼	43	73	73	73	81	81	81	81
1½	48	84	84	84	86	86	87	92
2	60	97	97	97	110	110	110	110
2½	76	110	110	109	129	129	129	124
3	89	129	129	129	148	148	148	143
3½	102	148	148	148	160	160	160	159
4	114	160	160	160	173	173	173	171
5	140	192	192	192	213	213	213	210
6	168	217	216	213	238	238	238	234
7	194	243	243	238	270	270	270	264
8	219	275	275	270	302	302	302	289
9	244	306	306	302	330	330	330	327
10	273	333	333	333	356	356	356	352
12	324	384	384	381	413	413	413	400
13	356	416	416	413	441	441	441	448
14	381	445	445	445	467	467	467	473
15	406	470	470	470	492	492	492	505
16	432	495	495	495	524	524	524	
17	457	527	527	527	556	556	556	
18	483	559	559	559	578	578	578	
19	508	584	584	584	610	610	610	
20	533	616	616	616	641	641	641	
21	559	648	648	645	667	667	667	
22	584	670	670	670	692	692	692	
23	610	695	695	695	721	721	721	
24	635	727	727	724	746	746	746	



## Full Face Gasket Dimensions as per BS 10

Table A

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	95	21	4	14	67
0.75	20	102	27	4	14	73
1	25	114	34	4	14	83
1.25	32	121	43	4	14	87
1.5	40	133	48	4	14	98
2	50	153	60	4	18	114
2.5	65	165	76	4	18	127
3	80	184	89	4	18	146
3.5	90	203	102	4	18	165
4	100	216	114	4	18	178
5	125	254	140	4	18	210
6	150	279	168	4	18	235
7	0	305	194	8	18	260
8	200	337	219	8	18	292
9	230	368	244	8	18	324
10	250	406	273	8	22	356
12	300	457	324	8	22	406
13	330	489	356	8	22	438
14	350	527	381	8	25	470
15	380	552	406	8	25	495
16	400	578	432	12	25	521
17	425	610	457	12	25	552
18	450	541	483	12	25	584
19	475	673	508	12	25	610
20	500	705	533	12	25	641
21	525	737	559	12	25	673
22	550	762	584	12	29	699
23	575	787	610	12	29	724
24	600	826	635	12	29	756



## Full Face Gasket Dimension as per BS 10

Table D

N-Bore		Full Face(mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	95	21	4	14	67
0.75	20	102	27	4	14	73
1	25	114	34	4	14	83
1.25	32	121	43	4	14	87
1.5	40	133	48	4	14	98
2	50	152	60	4	18	114
2.5	65	165	76	4	18	127
3	80	184	89	4	18	146
3.5	90	203	102	4	18	165
4	100	216	114	4	18	178
5	125	254	140	8	18	210
6	150	279	168	8	18	235
7	0	305	194	8	18	260
8	200	337	219	8	18	292
9	230	368	244	8	18	324
10	250	406	273	8	22	356
12	300	457	324	12	22	406
13	330	489	356	12	22	438
14	350	527	381	12	25	470
15	380	552	406	12	25	495
16	400	578	432	12	25	521
17	425	610	457	12	25	552
18	450	641	483	12	25	584
19	475	673	508	12	25	610
20	500	705	533	16	25	641
21	525	737	559	16	25	673
22	550	762	584	16	29	699
23	575	787	610	16	29	724
24	600	826	635	16	29	756



## Full Face Gasket Dimension as per BS 10

Table E

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	95	21	4	14	67
0.75	20	102	27	4	14	73
1	25	114	34	4	14	83
1.25	32	121	43	4	14	87
1.5	40	133	48	4	14	98
2	50	152	60	4	18	114
2.5	65	165	76	4	18	127
3	80	184	89	4	18	146
3.5	90	203	102	8	18	165
4	100	216	114	8	18	178
5	125	254	140	8	18	210
6	150	279	168	8	22	235
7	0	305	194	8	22	260
8	200	337	219	8	22	292
9	230	368	244	12	22	324
10	250	406	273	12	22	356
12	300	457	324	12	25	406
13	330	489	356	12	25	438
14	350	527	381	12	25	470
15	380	552	406	12	25	495
16	400	578	432	12	25	521
17	425	610	457	12	25	552
18	450	641	483	16	25	584
19	475	673	508	16	25	610
20	500	705	533	16	25	641
21	525	737	559	16	29	673
22	550	762	584	16	29	699
23	575	787	610	16	29	724
24	600	826	635	16	32	756



## Full Face Gasket Dimension as per BS 10

Table F

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	95	21	4	14	67
0.75	20	102	27	4	14	73
1	25	121	34	4	18	87
1.25	32	133	43	4	18	98
1.5	40	140	48	4	19	105
2	50	165	60	4	18	127
2.5	65	184	76	8	18	146
3	80	203	89	8	18	165
3.5	90	216	102	8	18	178
4	100	229	114	8	18	191
5	125	279	140	8	22	235
6	150	305	168	12	22	260
7	0	337	194	12	22	292
8	200	368	219	12	22	324
9	230	406	244	12	25	356
10	250	432	273	12	25	381
12	300	489	324	16	25	438
13	330	527	356	16	29	470
14	350	552	381	16	29	495
15	380	578	406	16	29	521
16	400	610	432	20	29	552
17	425	641	457	20	29	584
18	450	673	483	20	32	610
19	475	705	508	20	32	641
20	500	737	533	24	32	673
21	525	762	559	24	32	699
22	550	787	584	24	32	724
23	575	826	610	24	35	756
24	600	851	635	24	35	781



## Full Face Gasket Dimension as per BS 10

Table H

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	114	21	4	18	83
0.75	20	114	27	4	18	83
1	25	121	34	4	18	87
1.25	32	133	43	4	18	98
1.5	40	140	48	4	18	105
2	50	165	60	4	18	127
2.5	65	184	76	8	18	146
3	80	203	89	8	18	165
3.5	90	216	102	8	18	178
4	100	229	114	8	18	191
5	125	279	140	8	22	235
6	150	305	168	12	22	260
7	0	337	194	12	22	292
8	200	368	219	12	22	324
9	230	406	244	12	25	356
10	250	432	273	12	25	381
12	300	489	324	16	25	438
13	330	527	356	16	29	470
14	350	552	381	16	29	495
15	380	578	406	16	29	521
16	400	610	432	20	29	552
17	425	641	457	20	29	584
18	450	673	483	20	32	610
19	475	705	508	20	32	641
20	500	737	533	24	32	673
21	525	762	559	24	32	699
22	550	787	584	24	32	724
23	575	826	610	24	35	756
24	600	851	635	24	35	781



## Full Face Gasket Dimension as per BS 10

Table J

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	114	21	4	18	83
0.75	20	114	27	4	18	83
1	25	121	34	4	18	87
1.25	32	133	43	4	18	98
1.5	40	140	48	4	18	105
2	50	165	60	4	18	127
2.5	65	184	76	8	18	146
3	80	203	89	8	18	165
3.5	90	216	102	8	18	178
4	100	229	114	8	18	191
5	125	279	140	8	22	235
6	150	305	168	12	22	260
7	0	337	194	12	22	292
8	200	368	219	12	22	324
9	230	406	244	12	25	356
10	250	432	273	12	25	381
12	300	489	324	16	25	438
13	330	527	356	16	29	470
14	350	552	381	16	29	495
15	380	578	406	16	29	521
16	400	610	432	20	29	552
17	425	641	457	20	29	584
18	450	673	483	20	32	610
19	475	705	508	20	32	641
20	500	737	533	24	32	673
21	525	762	559	24	32	699
22	550	787	584	24	32	724
23	575	826	610	24	35	756
24	600	851	635	24	35	781



## Full Face Gasket Dimension as per BS 10

Table K

N-Bore		Full Face (mm)				
in	mm	OD	ID	Holes	Dia.	P.C.D.
0.5	15	114	21	4	18	83
0.75	20	114	27	4	18	83
1	25	127	34	4	18	95
1.25	32	133	43	4	18	98
1.5	40	152	48	4	22	114
2	50	165	60	8	18	127
2.5	65	184	76	8	22	146
3	80	203	89	8	22	165
3.5	90	229	102	8	25	184
4	100	241	114	8	25	197
5	125	279	140	12	25	235
6	150	305	168	12	25	260
7	0	343	191	12	29	292
8	200	368	216	12	29	318
9	230	406	241	16	29	356
10	250	432	270	16	29	381
12	300	489	321	16	29	432
13	330	546	346	16	35	483
14	350	572	371	16	35	508
15	380	603	397	20	35	540